



**B&T**

FABRICS &  
LEATHERS

GENUINE  
LEATHER

# Ocean

Real leather that has a pigmented and protective top coat with a soft handle and a silky matt finish.

GENUINE LEATHER


NUNANS

B&W


## OCEAN




401



434




436



435




433




404



406



408




437




438




441



440




431



417



420



423

Colors may slightly vary due to photographic lighting sources or your monitor settings.

## OCEAN



439



Colors may slightly vary due to photographic lighting sources or your monitor settings.

## OCEAN

### PRODUCT SPECIFICATIONS

| Technical Informations                         | Unit       |           | Value          | Test Method                            |
|--|------------|-----------|----------------|--|
| Tear Strength                                  | n          | >=20      |                | UNI EN ISO 3377-1                      |
| Colour Fastness to Rubbing Dry                 | grey scale | >=4       | 500 cycles     | UNI EN ISO 11640:1998                  |
| Colour Fastness to Rubbing Wet                 | grey scale | >=4       | 250 cycles     | UNI EN ISO 11640:1998                  |
| Colour Fastness to Rubbing Sweat               | grey scale | >=4       | 80 cycles      | UNI EN ISO 11640:1998<br>ISO 11641 pH8 |
| Flexing Endurance / Dry                        |            | no damage | 50.000 cycles  | UNI EN ISO 5402                        |
| Dinish Adhesion / Dry                          | n/cm       | >=2       |                | UNI EN ISO 11644                       |
| Colour Fastness to Artificial Light Exposition | blue scale | >=5       | 16.000 kj/sqm. | UNI EN ISO 105 B02 (MET,5)             |
| Burning Behaviour to Cigarette and Match Fami  |            |           |                | BS 5852:1979                           |

Bovine of European origin, corrected and embossed for enhanced grain consistency. Thickness is 0,8 – 1,0 mm. Average size of each hide is around 3,8 – 4,0 sqm. Finished using water based system. This product has a pigmented and protective top coat, with a soft handle and a silky matt finish.